1

2

4.

AMENDMENTS TO THE CLAIMS

This listing of claims replaces all prior versions, and listings, of claims in the application:

1 1. (Currently Amended) A method of interleaving speech data communicated with a 2 particular mobile station over a plurality of frames, comprising: 3 interleaving a first set of the speech data communicated in a communications session with the particular mobile station according to a first algorithm over plural frames 4 5 communicated over a wireless channel for a first set of speech data; and 6 interleaving a second set of the speech data communicated in the communications session with the particular mobile station according to a second algorithm over plural frames 7 8 communicated over the wireless channel for a second set of speech data. 1 2. (Cancelled) (Previously Presented) The method of claim 1, wherein interleaving the speech 1 3. data according to the first or second algorithm comprises interleaving over frames of a 2 3 multiframe.

(Original) The method of claim 3, wherein interleaving over frames of the

multiframe comprises interleaving over a General Packet Radio Service multiframe.

2

5. (Previously Presented) A method of interleaving data over a plurality frames, 1 2 comprising: 3 interleaving the data according to a first algorithm over plural frames communicated over a wireless channel for a first set of data; and 4 5 interleaving the data according to a second algorithm over plural frames communicated over the wireless channel for a second set of data, 6 wherein interleaving the data according to the first or second algorithm comprises 7 8 interleaving over frames of a multiframe, 9 wherein the multiframe comprises plural blocks, each block having four frames, each frame containing plural bursts, and the data is carried in data frame N starting in block B(x), 10 and wherein interleaving the data frame N according to the first and second algorithms comprises 11 12 interleaving the data frame N over blocks B(x + 2k) and B(x + 2k + 2), where k = INT(N/2). 6. (Original) The method of claim 5, wherein interleaving the data according to the 1 first algorithm comprises interleaving the data frame N over bursts in the last three frames in 2 block B(x + 2k) and the first frame in block B(x + 2k + 2), if N is even. 3 7. (Original) The method of claim 6, wherein interleaving the data according to the 1 second algorithm comprises interleaving the data frame N over bursts in the last frame in block 2 B(x + 2k) and the first three frames in block B(x + 2k + 2), if N is odd. 3 (Original) The method of claim 7, wherein interleaving the data according to the 8. 1 2 first and second algorithms comprises interleaving speech data. 1 9. (Original) The method of claim 8, wherein interleaving the speech data 2 comprises interleaving speech data of a half-rate mobile station.

1	10.	(Original) The method of claim 7, further comprising:	
2		receiving an end-of-data indicating frame to indicate that the data frame N is the	
3	last data frame; and		
4		interleaving the end-of-data indicating frame over bursts in the last frame in block	
5	B(x + 2k) and	If the first two frames of block $(Bx + 2k + 2)$, if M is even.	
1	11.	(Original) The method of claim 10, further comprising repeating the end-of-data	
2	indicating fra	me over bursts in the last two frames of block $B(x + 2k + 2)$.	
1	12.	(Original) The method of claim 10, further comprising interleaving the end-of-	
2	data indicatin	g frame over bursts in the last three frames of block $B(x + 2k + 2)$, if M is odd.	
1	13.	(Original) The method of claim 3, wherein the multiframe comprises plural	
2	blocks and ea	sch block comprises plural frames, each frame containing plural bursts, the data	
3	being carried in data frames interleaved over bursts in the plural frames, the method further		
4	comprising:		
5		receiving an end-of-data indicating frame to indicate that a data frame is the last	
6	data frame; a	nd .	
7		interleaving the end-of-data indicating frame according to predetermined	
8	algorithms,		
9		wherein interleaving the data frames according to the first and second algorithms	
10	and the end-o	of-data indicating frame according to the predetermined algorithms enables the end-	
11	of-data indica	ating frame to end within the same block carrying the last data frame.	

1	14.	(Previously Presented) A method of interleaving data over a plurality frames,
2	comprising:	
3		interleaving the data according to a first algorithm over plural frames
4	communicate	d over a wireless channel for a first set of data; and
5		interleaving the data according to a second algorithm over plural frames
6	communicate	d over the wireless channel for a second set of data,
7		wherein interleaving the data according to the first or second algorithm comprises
8	interleaving over frames of a multiframe,	
9		wherein the multiframe comprises plural blocks and each block comprises plural
10	frames, each	frame containing plural bursts, the data being carried in data frames interleaved
11	over bursts in	the plural frames, the method further comprising:
12		receiving an end-of-data indicating frame to indicate that a data frame is the last
13	data frame; and	
14		interleaving the end-of-data indicating frame according to at least one
15	predetermined algorithm,	
16		wherein interleaving the data frames according to the first and second algorithms
17	and the end-o	f-data indicating frame according to the at least one predetermined algorithm
18	enables the en	nd-of-data indicating frame to end within the same block carrying the last data
19	frame,	
20		wherein the last data frame is data frame M starting in block B(x), wherein, if M
21	is odd, interle	aving the data frame M comprises interleaving the data frame M over bursts in the
22	last frame in block $B(x)$ and the first three frames of $B(x + 2)$, and wherein interleaving the end-	
23 -	of-data indicating frame comprises interleaving the end-of-data indicating frame over bursts in	
24	the last three	frames of block $B(x + 2)$.
1	15.	(Original) The method of claim 14, wherein, if M is even, interleaving the data
2	frame M com	prises interleaving the data frame M over bursts in the last three frames in block
3	B(x) and first	frame in block $B(x + 2)$, and interleaving the end-of-data indicating frame
4	comprises int	erleaving the end-of-data indicating frame over bursts in the last frame in block
5	B(x) and first two frames in block $B(x + 2)$.	

(Original) The method of claim 15, wherein the end-of-data indicating frame 1 16. comprises a SID_FIRST frame according to a General Packet Radio Service protocol. 2 17. (Cancelled) 1 (Previously Presented) The system of claim 38, wherein the first and second data 1 18. 2 frames comprise respective first and second speech frames. (Previously Presented) The system of claim 38, wherein each data frame is 19. 1 2 interleaved over four bursts. (Previously Presented) A system for communicating over a wireless channel in a 1 20. mobile communications network, comprising: 2 an interface adapted to receive traffic data frames from a half-rate mobile station; 3 4 and a controller adapted to process a first data frame interleaved over plural bursts 5 according to a first algorithm and to process a second data frame interleaved over plural bursts 6 7 according to a second algorithm, wherein the bursts are part of a multiframe, the multiframe comprising plural 8 blocks, each block comprising four bursts, and wherein data frames I, I = 0 to M, are received 9 starting in block B(x), the controller adapted to interleave data frame I over blocks B(x + 2k)10 11 and B(x + 2k + 2), where k = INT(I/2). 1 21. (Original) The system of claim 20, wherein the controller is adapted to: 2 for I being even, interleave traffic data frame I over the last three bursts in block 3 B(x + 2k) and the first burst in block B(x + 2k + 2); and for I being odd, interleave traffic data frame I over the last three bursts in block 4 5 B(x + 2k) and the first burst in block B(x + 2k + 2).

(Original) The system of claim 21, wherein the interface is adapted to further 22. 1 2 receive an end-of-data indicating frame, the end-of-data indicating frame interleaved a first way if M is even and a second way if M is odd. 3 (Original) The system of claim 22, wherein the controller is adapted to: 23. 1 for M being even, interleave the end-of-data indicating frame over the last burst in 2 3 block B(x + 2k) and the first two bursts in block B(x + 2k + 2); and for M being odd, interleave the end-of-data indicating frame over the last three 4 5 bursts of B(x + 2k + 2). (Original) The system of claim 23, wherein the end-of-data indicating frame 24. 1 2 comprises a SID_FIRST frame according to a General Packet Radio Service protocol. 25. (Original) The system of claim 23, wherein the end-of-data indicating frame 1 indicates that discontinuous transmission mode is starting. 2 (Original) The system of claim 23, wherein the traffic data frames are carried in a 1 26. wireless channel portion, the interface adapted to receive traffic data frames from another mobile 2 3 station in block B(x + 2k + 4). (Original) The system of claim 26, wherein the traffic data frames from the half-1 27. 2 rate mobile station comprises speech data.

30. (Cancelled)

mobile station comprises another type of data.

1

2

1

2

1

28.

29.

full-rate mobile station.

(Original) The system of claim 27, wherein the traffic data frames from the other

(Original) The system of claim 27, wherein the other mobile station comprises a

1	31.	(Previously Presented) The article of claim 39, wherein the instructions when		
2	executed cause the system to:			
3		receive speech traffic from the first mobile station over the wireless channel		
4	portion.			
1	32.	(Original) The article of claim 31, wherein the instructions when executed cause		
2	the system to	receive another type of traffic from the second mobile station.		
1	33.	(Previously Presented) The article of claim 39, wherein the instructions when		
2	executed cau	se the system to interleave a first traffic frame from the first mobile station over		
3	plural bursts	according to a first algorithm and to interleave a second traffic frame from the first		
4	mobile static	on over plural bursts according to a second algorithm.		
1	34.	(Currently Amended) A data signal embodied in a carrier wave and containing		
2	An article co	mprising at least one storage medium containing instructions that when executed		
3	cause a syste	m to:		
4		interleave a first speech traffic frame [[from]] in a communications session of a		
5	mobile statio	on over plural bursts according to a first algorithm; and		
6		interleave a second speech traffic frame [[from]] in the communications session		
7	of the mobile	e station over plural bursts according to a second algorithm.		
1	35.	(Cancelled)		

1	36. (Currently Amended) The method of claim 1, A method of interleaving speech	
2	data over a plurality of frames, comprising:	
3	interleaving the speech data according to a first algorithm over plural frames	
4	communicated over a wireless channel for a first set of speech data; and	
5	interleaving the speech data according to a second algorithm over plural frames	
6	communicated over the wireless channel for a second set of speech data,	
7	wherein interleaving the speech data according to the first algorithm over plura	
8	frames for the first set of speech data comprises interleaving the first set of speech data from a	
9	half-rate mobile station according to the first algorithm over plural frames, and	
10	wherein interleaving the speech data according to the second algorithm over	
11	plural frames for the second set of speech data comprises interleaving the second set of speech	
12	data from a half-rate mobile station according to the second algorithm over plural frames.	
1	37. (Previously Presented) The system of claim 38, wherein the bursts are part of a	
2	multiframe, the multiframe having plural blocks,	
3	wherein the first data frame n is interleaved according to the first algorithm by	
4	interleaving the first data frame n in bursts of two different blocks, the two different blocks	
5	selected based on n being an even number, and	
6	wherein the second data frame $n + 1$ is interleaved according to the second	
7	algorithm by interleaving the second data frame n + 1 in bursts of two different blocks, the two	
8	different blocks selected based on n + 1 being an odd number.	

1	38.	(Previously Presented) A system for communicating over a wireless channel in a	
2	mobile communications network, comprising:		
3		an interface adapted to receive traffic data frames from a half-rate mobile station;	
4	and		
5		a controller adapted to process a first data frame n, n being an even number, from	
6	the half-rate mobile station interleaved over plural bursts according to a first algorithm and to		
7	process a second data frame n + 1, n + 1 being an odd number, from the half-rate mobile station		
8	interleaved over plural bursts according to a second algorithm,		
9		wherein the first data frame n is interleaved according to the first algorithm in	
10	response to n	being an even number, and the second data frame is interleaved according to the	
11	second algorithm in response to n + 1 being an odd number.		
. 1	39.	(Previously Presented) An article comprising at least one storage medium	
2	containing in	structions that when executed cause a system to:	
3		receive traffic over a wireless channel portion from a first mobile station involved	
4	in half-rate co	ommunication;	
5		detect that the first mobile station has entered discontinuous transmission mode;	
6		in response to detecting that the first mobile station has entered discontinuous	
7	transmission mode, re-assign the wireless channel portion to a second mobile station to enable		
8	multiplexing of traffic from the second mobile station onto the wireless channel portion while th		
9	first mobile s	tation is in discontinuous transmission mode;	
10		receive a request from the first mobile station to re-acquire the wireless channel	
11	portion, the request transmitted by the first mobile station in response to the first mobile station		
12	exiting discontinuous transmission mode; and		
13		sending an assignment message to the first mobile station to assign the wireless	
14	channel porti	on in response to the request.	

	40. (Currently Amended) The data signal article of claim 34, wherein interleaving	ng	
	the first speech traffic frame according to the first algorithm over plural bursts comprises		
	interleaving the first speech traffic frame from a half-rate mobile station according to the fir	st	
algorithm over plural bursts, and			
	wherein interleaving the second speech traffic frame according to the second	l	
	algorithm over plural bursts comprises interleaving the second speech traffic frame from a h	ıalf-	
	rate mobile station according to the second algorithm over plural bursts.		
	41. (Previously Presented) A system for use in a mobile communications network	rk,	
	comprising:		
	a wireless interface adapted to receive traffic over a wireless channel portion	from	
	a first mobile station involved in half-rate communications; and		
	a controller adapted to receive an indication that the first mobile station has		
	entered discontinuous transmission mode and, in response to receiving the indication that the	e	
	first mobile station has entered discontinuous transmission mode, to multiplex traffic from a	ì	
	second mobile station onto the wireless channel portion while the first mobile station is in		
	discontinuous transmission mode,		
	wherein the controller is adapted to further:		
	receive a request from the first mobile station to re-acquire the wireless channels	nel	
	portion, the request transmitted by the first mobile station in response to the first mobile stat	tion	
	exiting discontinuous transmission mode; and		
	send an assignment message to the first mobile station to assign the wireless		
	channel portion in response to the request.		